

精密キヤホンプの仕様

| 型式 | 容量範囲 (L/min) | 最高圧力 (MPa) | 用途 | | | | | | |
|-----------|-----------------|---------------|----|------|-------|----|-------|------|---|
| | | | 計量 | 押出成形 | 高品位成形 | 重合 | 真空拔出し | 化学繊維 | |
| KAP-1 KA1 | 0.015~0.6 | 6.9 | ◎ | | | | | | ◎ |
| KA3 | 0.03~1.1 | 6.9 | ◎ | | | | | | ◎ |
| KA4 | 0.15~4.5 | 6.9 | ◎ | | | | | | ◎ |
| BAS | 0.06~3 | 29.4 | ◎ | ○ | | | | | ◎ |
| | | 24.5 | | | | | | | |
| | | 19.6 | | | | | | | |
| BAS-H | 0.06~2 | 49 | | ◎ | | | | | ◎ |
| KH5 | 0.2~6 | 19.6 | ◎ | ○ | | | | | ◎ |
| KES | 0.8~20 | 14.7 | ○ | ○ | | | | | ◎ |
| PFS | 0.25~15 | 7.8 | ◎ | | | | | | ◎ |
| KHP-1H | 0.001~0.24 | 49 | ○ | ◎ | | | | | ◎ |
| HF | 0.1~40 | 39.2 | | ◎ | | | | | |
| HB | 2~60 | 39.2 | | | | | ◎ | | |
| HBT | 0.1~90 | 29.4 | | | ◎ | | | | |
| HBTD | 0.1~72 | 29.4 | | | ◎ | | | | |
| HBTDS | 0.1~40 | 2.9 | ◎ | | | | | | |
| HT | 0.02~160 | 29.4 | | ○ | | | ◎ | ◎ | |
| B | 3~800 | 4.9 | | | | | ○ | | ◎ |