

## JIS Q 17050-1 に基づく自己適合宣言書 (QC -17043 付属書-1)

| 型番            | 冷凍                     |                        |                           | 加熱                     |                        |                           | 性能確認方法<br>の区分 | 分類名   |
|---------------|------------------------|------------------------|---------------------------|------------------------|------------------------|---------------------------|---------------|-------|
|               | 定格能力<br>(標準定格)<br>[kW] | 消費電力<br>(標準定格)<br>[kW] | 加熱源消費熱量<br>(標準定格)<br>[kW] | 定格能力<br>(標準定格)<br>[kW] | 消費電力<br>(標準定格)<br>[kW] | 加熱源消費熱量<br>(標準定格)<br>[kW] |               |       |
| NZ(G,P)-80H   | 281                    | 2.65                   | 186                       | 186                    | 2.35                   | 186                       | B-2           | 二重効用形 |
| NZ(G,P)-100H  | 352                    | 2.65                   | 233                       | 232                    | 2.35                   | 233                       |               |       |
| NZ(G,P)-120H  | 422                    | 3.00                   | 279                       | 278                    | 2.70                   | 279                       |               |       |
| NZ(G,P)-150H  | 528                    | 3.00                   | 349                       | 348                    | 2.70                   | 349                       |               |       |
| NZ(G,P)-180H  | 633                    | 4.10                   | 418                       | 417                    | 3.80                   | 418                       |               |       |
| NZ(G,P)-210H  | 739                    | 4.10                   | 488                       | 487                    | 3.80                   | 488                       |               |       |
| NZ(G,P)-250H  | 879                    | 4.85                   | 579                       | 580                    | 4.55                   | 579                       |               |       |
| NZ(G,P)-300H  | 1055                   | 5.60                   | 697                       | 696                    | 5.30                   | 697                       |               |       |
| NZ(G,P)-360H  | 1266                   | 5.70                   | 837                       | 835                    | 5.30                   | 837                       |               |       |
| NZ(G,P)-400H  | 1407                   | 6.40                   | 930                       | 928                    | 6.00                   | 930                       |               |       |
| NZ(G,P)-450H  | 1583                   | 6.40                   | 1044                      | 1044                   | 6.00                   | 1044                      |               |       |
| NZ(G,P)-500H  | 1759                   | 7.80                   | 1162                      | 1160                   | 7.40                   | 1162                      |               |       |
| NZ(G,P)-560H  | 1970                   | 9.80                   | 1302                      | 1299                   | 9.40                   | 1302                      |               |       |
| NZ(G,P)-630H  | 2216                   | 9.80                   | 1465                      | 1461                   | 9.40                   | 1465                      |               |       |
| NZ(G,P)-700H  | 2462                   | 9.80                   | 1627                      | 1623                   | 9.40                   | 1627                      |               |       |
| NZ(G,P)-800H  | 2813                   | 13.50                  | 1860                      | 1855                   | 13.10                  | 1860                      |               |       |
| NZ(G,P)-900H  | 3165                   | 13.50                  | 2092                      | 2087                   | 13.10                  | 2092                      |               |       |
| NZ(G,P)-1000H | 3517                   | 17.30                  | 2325                      | 2319                   | 16.90                  | 2325                      |               |       |

※ ( )内はいずれかの文字が入ります。例: NZ(G,P)⇒NZGまたはNZP

## JIS Q 17050-1 に基づく自己適合宣言書 (QC -17043 付属書-1)

| 型番            | 冷凍                     |                        |                           | 加熱                     |                        |                           | 性能確認方法<br>の区分 | 分類名   |
|---------------|------------------------|------------------------|---------------------------|------------------------|------------------------|---------------------------|---------------|-------|
|               | 定格能力<br>(標準定格)<br>[kW] | 消費電力<br>(標準定格)<br>[kW] | 加熱源消費熱量<br>(標準定格)<br>[kW] | 定格能力<br>(標準定格)<br>[kW] | 消費電力<br>(標準定格)<br>[kW] | 加熱源消費熱量<br>(標準定格)<br>[kW] |               |       |
| NZ(G,P)-80A   | 281                    | 2.65                   | 189                       | 186                    | 2.35                   | 186                       | B-2           | 二重効用形 |
| NZ(G,P)-100A  | 352                    | 2.65                   | 235                       | 232                    | 2.35                   | 233                       |               |       |
| NZ(G,P)-120A  | 422                    | 3.00                   | 283                       | 278                    | 2.70                   | 279                       |               |       |
| NZ(G,P)-150A  | 528                    | 3.00                   | 354                       | 348                    | 2.70                   | 349                       |               |       |
| NZ(G,P)-180A  | 633                    | 4.10                   | 424                       | 417                    | 3.80                   | 418                       |               |       |
| NZ(G,P)-210A  | 739                    | 4.10                   | 494                       | 487                    | 3.80                   | 488                       |               |       |
| NZ(G,P)-250A  | 879                    | 4.85                   | 588                       | 580                    | 4.55                   | 579                       |               |       |
| NZ(G,P)-300A  | 1055                   | 5.60                   | 707                       | 696                    | 5.30                   | 697                       |               |       |
| NZ(G,P)-360A  | 1266                   | 5.70                   | 849                       | 835                    | 5.30                   | 837                       |               |       |
| NZ(G,P)-400A  | 1407                   | 6.40                   | 947                       | 928                    | 6.00                   | 930                       |               |       |
| NZ(G,P)-450A  | 1583                   | 6.40                   | 1060                      | 1044                   | 6.00                   | 1044                      |               |       |
| NZ(G,P)-500A  | 1759                   | 7.80                   | 1182                      | 1160                   | 7.40                   | 1162                      |               |       |
| NZ(G,P)-560A  | 1970                   | 9.80                   | 1324                      | 1299                   | 9.40                   | 1302                      |               |       |
| NZ(G,P)-630A  | 2216                   | 9.80                   | 1491                      | 1461                   | 9.40                   | 1465                      |               |       |
| NZ(G,P)-700A  | 2462                   | 9.80                   | 1657                      | 1623                   | 9.40                   | 1627                      |               |       |
| NZ(G,P)-800A  | 2813                   | 13.50                  | 1892                      | 1855                   | 13.10                  | 1860                      |               |       |
| NZ(G,P)-900A  | 3165                   | 13.50                  | 2130                      | 2087                   | 13.10                  | 2092                      |               |       |
| NZ(G,P)-1000A | 3517                   | 17.30                  | 2358                      | 2319                   | 16.90                  | 2325                      |               |       |

※ ( )内はいずれかの文字が入ります。例: NZ(G,P)⇒NZGまたはNZP